

August 16, 2005  
Response to Office Action of July 18, 2005  
Application: 10/717,627 November 21, 2003  
File No. 2993-483US CMB/cb

### Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

### Listing of claims:

1. (original) An engine shutdown device for controlling a fuel shut-off valve to thereby selectively interrupt fuel flow to an engine, said device comprising:
  - a normal switch connected to said fuel shut-off valve and configured to respond to at least one of a normal shutdown signal and an emergency shutdown signal;
  - an emergency switch connected to said fuel shut-off valve and configured to respond to said emergency shutdown signal having transient characteristics;
  - wherein, upon receipt of said emergency shutdown signal, said emergency switch sends an emergency interruption signal to said valve and said normal switch send a normal interruption signal to said valve to thereby interrupt said fuel flow; and
  - said normal interruption signal having a given normal value, and said emergency interruption signal having a peak value substantially larger than said given normal value, whereby said fuel flow interrupting occurs faster in response to said emergency shutdown signal than in response to said normal shutdown signal.
2. (original) The device of claim 1, further comprising a manual switch connected to said fuel shut-off valve for selectively interrupting said fuel flow in response to a manual shutdown signal being independent of said normal shutdown signal and said emergency shutdown signal.
3. (original) The device of claim 1, wherein said normal switch and said emergency switch each comprise a transistor and said given normal value and said peak value comprise voltage values.

August 16, 2005  
Response to Office Action of July 18, 2005  
Application: 10/717,627 November 21, 2003  
File No. 2993-483US CMB/cib

4. (original) The device of claim 1, further comprising a safety switch connected to said fuel shut-off valve and configured to respond to at least one of a second normal shutdown signal, and a second emergency shutdown signal, said second normal and emergency shutdown signals provided from a source which is different from a source for said normal and emergency shutdown signals.
5. (original) A gas turbine engine comprising an engine shutdown device for controlling a fuel shut-off valve to thereby selectively interrupt fuel flow to said engine, said device comprising:

a normal switch connected to said fuel shut-off valve and configured to respond to at least one of a normal shutdown signal and an emergency shutdown signal;

an emergency switch connected to said fuel shut-off valve and configured to respond to said emergency shutdown signal having transient characteristics;

wherein, upon receipt of said emergency shutdown signal, said emergency switch sends an emergency interruption signal and said normal switch sends a normal interruption signal to said valve to thereby interrupt said fuel flow; and

said normal interruption signal having a given normal value and said emergency interruption signal having a peak value substantially larger than said given normal value, whereby said fuel flow interrupting occurs faster in response to said emergency shutdown signal than in response to said normal shutdown signal.

6. (original) The gas turbine engine of claim 5, further comprising a manual switch connected to said fuel shut-off valve for selectively interrupting said fuel flow in response to a manual shutdown signal being independent of said normal shutdown signal and said emergency shutdown signal.

August 16, 2005

Response to Office Action of July 18, 2005

Application: 10/717,527 November 21, 2003

File No. 2993-483US CMB/clb

7. (original) The gas turbine engine of claim 5, wherein said normal switch and said emergency switch each comprise a transistor and said given normal value and said peak value comprise voltage values.
8. (original) The gas turbine engine of claim 5, further comprising a safety switch connected to said fuel shut-off valve and configured to respond to at least one of a second normal shutdown signal, and a second emergency shutdown signal, said second normal and emergency shutdown signals provided from a source which is different from a source for said normal and emergency shutdown signals.

9-11.(cancelled)